

FEBRUARY 2, 2010

TK-1450 ANTI-GRAFFITI PRIMER

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-1450 ANTI-GRAFFITI PRIMER is a urethane dispersion for use under Permaclean Anti-Graffiti Coatings. It will reduce or eliminate the darkening or color change that occurs when Permaclean is applied to masonry surfaces, protect latex coatings from lifting and bleeding, and reduce the penetration of Permaclean into the substrate helping to insure a continuous film for graffiti protection.

TK Products certifies the following information for TK-1450 ANTI-GRAFFITI PRIMER:

Manufacturing Location

TK-1450 ANTI-GRAFFITI PRIMER is manufactured in Minnetonka, MN.

Regional Materials

21% by weight of TK-1450 ANTI-GRAFFITI PRIMER was produced with regionally extracted and processed materials.

Recycled Content

TK-1450 ANTI-GRAFFITI PRIMER is manufactured with 6% combined recycled content.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-1450 ANTI-GRAFFITI PRIMER is 346g/l.

Based upon the above information, TK Products certifies that TK-1450 ANTI-GRAFFITI PRIMER may contribute to the following LEED NC v2.2 Credits:

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- SS Credit 5.1: Site Development: Protect or Restore Habitat

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council