

APRIL 4, 2009

TK-9000 EPOXY CRACK FILLER

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-9000 EPOXY CRACK FILLER is a two-component epoxy designed to fill and seal cracks in floors and decking for both interior and exterior applications. TK-9000 EPOXY CRACK FILLER cures fast, but remains somewhat flexible and maintains elongation for moving cracks. It is low viscosity and pourable and can be applied by a variety of pourable application equipment.

TK Products certifies the following information for TK-9000 EPOXY CRACK FILLER:

Manufacturing Location

TK-9000 EPOXY CRACK FILLER is manufactured in Minnetonka, MN.

Regional Materials

20% by weight of TK-9000 EPOXY CRACK FILLER was produced with regionally extracted and processed materials.

Recycled Content

TK-9000 EPOXY CRACK FILLER is manufactured with 6% combined recycled content.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-9000 EPOXY CRACK FILLER is 0g/l.

Based upon the above information, TK Products certifies that TK-9000 EPOXY CRACK FILLER may contribute to the following LEED NC v2.2 Credits:

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- EQ Credit 4.2: Low –Emitting Material: Paint and Coating (referencing the South Coast Air Quality Management District (SCAQMD) Rule 1113, in effect on January 1, 2004)

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council