

JANUARY 27, 2010

TK-2671 EPOXY WATERPROOFING TREATMENT

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TK-2671 EPOXY WATERPROOFING TREATMENT is a two-component epoxy/polyamide waterproofing treatment for concrete. It protects new and existing concrete from deterioration caused by moisture, deicing chemicals, grease, oil, and freeze thaw cycles. TK-2671 meets and/or exceeds the following: ASTM C-140 Water Absorption; ASTM C-507 Wear Surface Strength; ASTM C-672 Scaling; MN, IA, OH, Dept. of Transportation Special Test Evaluations.

TK Products certifies the following information for TK-2671 EPOXY WATERPROOFING TREATMENT:

Manufacturing Location

TK-2671 EPOXY WATERPROOFING TREATMENT is manufactured in Minnetonka, MN.

Regional Materials

30% by weight of TK-2671 EPOXY WATERPROOFING TREATMENT was produced with regionally extracted and processed materials.

Recycled Content

TK-2671 EPOXY WATERPROOFING TREATMENT is manufactured with 6% combined recycled content.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TK-2671 EPOXY WATERPROOFING TREATMENT is 600g/l.

Based upon the above information, TK Products certifies that TK-2671 EPOXY WATERPROOFING TREATMENT may contribute to the following LEED NC v2.2 Credits:

- MR Credits 1.1 & 1.2: Building Reuse: Maintain 75% & 95% of Existing Walls, Floors, & Roof
- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council