

March 31, 2020

[TK-AIRMAX 2102 NON-PERMEABLE AIR/VAPOR BARRIER](#)

***Product Information Statement for LEED® v.4 Credit Documentation***

TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER is a spray applied flexible air/vapor barrier membrane for all types of cavity wall construction. It meets or exceeds ASTM E-2178 for air leakage and ASTM E-96 for water vapor permeability.

Use of air barrier systems may contribute to the attainment of LEED® Energy and Atmosphere and Indoor Environmental Quality credits as part of the overall building design.

***TK Products certifies the following information for TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER:***

**MR Credit Building Product Disclosure and Optimization- Environmental Product Declarations**

An Environmental Product Declaration (EPD) is not available for TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER.

**MR Credit Building Product Disclosure and Optimization- Sourcing of Raw Materials**

Raw Material Source and Extraction Reporting is not available for TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER. TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER is manufactured in Minnetonka, MN.

TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER is manufactured with 6% recycled/bio-based materials.

**EQ Credit Low-Emitting Materials**

TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER has a VOC content of 547g/l. It is compliant under the U.S. National AIM rule. TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER does not meet the VOC requirements set forth by LADCO, OTC, CARB, and SCAQMD.

Emissions Test Reporting is not available for TK-AIRMAX® 2102 NON-PERMEABLE AIR/VAPOR BARRIER



Respectfully,

LEED Administrator  
TK Products  
Tel: 800-441-2129

***LEED is a trade mark of the US Green Building Council***

ADVANCED CONCRETE COATING SOLUTIONS