

March 31, 2020

[TK-2105 AIRMAX VP® AIR BARRIER](#)

***Product Information Statement for LEED® v.4 Credit Documentation***

TK-2105 AIRMAX VP® AIR BARRIER is a high solids, solvent-borne, elastomeric spray applied flexible air barrier, water vapor permeable membrane for all types of cavity wall construction. It meets or exceeds ASTM E-2178 for air leakage and ASTM E-96 for water vapor permeability.

Use of air barrier systems may contribute to the attainment of LEED® Energy and Atmosphere and Indoor Environmental Quality credits as part of the overall building design.

***TK Products certifies the following information for TK-2105 AIRMAX VP® AIR BARRIER:***

**MR Credit Building Product Disclosure and Optimization- Environmental Product Declarations**

An Environmental Product Declaration (EPD) is not available for TK-2105 AIRMAX VP® AIR BARRIER.

**MR Credit Building Product Disclosure and Optimization- Sourcing of Raw Materials**

Raw Material Source and Extraction Reporting is not available for TK-2105 AIRMAX VP® AIR BARRIER. TK-2105 AIRMAX VP® AIR BARRIER is manufactured in Minnetonka, MN.

TK-2105 AIRMAX VP® AIR BARRIER is manufactured with <1% recycled/bio-based materials.

**EQ Credit Low-Emitting Materials**

TK-2105 AIRMAX VP® AIR BARRIER has a VOC content of 100 g/L. It is compliant under the U.S. National AIM rule, LADCO, OTC Phase I, and CARB 2000 SCM. TK-2105 AIRMAX VP® AIR BARRIER does not meet the VOC requirements set forth by OTC Phase II, CARB 2007 SCM, & SCAQMD.

Emissions Test Reporting is not available for TK-2105 AIRMAX VP® AIR BARRIER.



Respectfully,

LEED Administrator  
TK Products  
Tel: 800-441-2129

*LEED is a trade mark of the US Green Building Council*

ADVANCED CONCRETE COATING SOLUTIONS