

PRODUCT DESCRIPTION

TK-DOT STAIN is a high solids, pigmented chlorinated rubber that cures, seals and protects previously patched or mismatched concrete. TK-DOT masks surface inconsistencies while imparting a uniform and attractive finish that is protected from the elements. Available in standard colors. TK-DOT STAIN is specifically formulated for Department of Transportation (DOT) projects.

Features:

- Hides concrete color variations/shading due to placement and finishing procedures.
- Superior to simple coating products in that it covers surface inconsistencies and allows for good penetration and adhesion with the surface.
- Prevents pop-outs on patched concrete by sealing surfaces off from water and chemical intrusion.
- Provides excellent resistance to abrasion and chemical attack.
- Compatible with most chlorinated rubber or acrylic based curing and sealing compounds.
- Does not yellow or discolor.

USES:

Suitable for interior or exterior use on vertical concrete surfaces that have been previously patched or where mismatched concrete is present (for horizontal applications, see TK-CCS CONCRETE COLORED STAIN*). For Department of Transportation (DOT) projects such as: "J" barrier walls, abutment walls, beams, columns, etc.

APPLICATION PROCEDURES:

PREPARATION:

Surfaces must be free of oils, grease, form release agents, curing compounds or soil. Repair all existing cracks, scaling or spalled areas and remove incompatible coatings and curing compounds with strippers or power equipment. Clean surfaces with Trisodium Phosphate or other suitable concrete cleaning agent, rinse thoroughly and allow to dry.

MIXING:

- 1) Mix using a mechanical paint paddle-type mixer for 3-5 minutes until color is completely and uniformly suspended throughout the material.
- 2) Removal of the container cover is recommended while mixing to ensure that all material is mixed properly and all pigment appropriately distributed.

APPLICATION:

TK-DOT STAIN may be applied by airless spray, brush or long nap roller. Spray is most cost effective, followed by back rolling to evenly distribute the color. Avoid puddling and heavy accumulations.

CLEAN UP:

Use TK-00 XYLENE* to clean tools and equipment. Pump solvent through the sprayer to remove residue of materials

TECHNICAL DATA

Composition and Materials:	Chlorinated rubber with a fast drying aromatic solvent.
Flash Point:	81°F
Drying Time	
Tack Free:	30 minutes
Open to Traffic:	1 hour
VOC Content:	< 700 g/l
A.I.M. Category:	Concrete Curing and Sealing Compounds Maximum VOC 700 g/l
Applicable Standards:	- ASTM C-1315, Type 1, Class B & C - ASTM C-309, Type 1, Class A & B and Type 1D with a red dye added. - Fed. TTC-C-800A, Type 1, Class 1 - AASHTO Des. M-148, Type 1, Clear - DE CRD - C-300

which can clog the hose and wand assembly.

COVERAGE:

Typical coverage rate is 200-300 square feet per gallon. If a second coat is desired, apply at 300-400 square feet per gallon. Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

MAINTENANCE:

Minimal maintenance is required other than occasional sweeping, dusting or mopping. If wear patterns occur or if spillage removes the coating, TK-DOT STAIN may be reapplied to the affected area(s).

LIMITATIONS:

- Apply in temperatures above 40°F. Colder weather applications may be made under prescribed conditions and procedures specified by TK Products.
- Not for use on asphalt or surfaces subjected to immersion or constant liquid contact.
- As with all colored coatings, this product will be a maintenance item that requires occasional recoating (recoating schedule will be dependent on the severity of use).

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-DOT STAIN is available through TK Distributors. Contact TK Products for the nearest distributor.

Available in standard colors.

Packaged in 55-gallon drums, 5-gallon pails and 1-gallon cans.

FOR PROFESSIONAL USE ONLY

NOTES:

*TK-CCS CONCRETE COLORED STAIN must be purchased separately

*TK-00 XYLENE must be purchased separately

03/15 Last Rev. 09/14

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED. TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.



TK Products Construction Coatings

11400 West 47th Street Minnetonka, MN 55343

800-441-2129 toll free | 952-938-8084 fax | www.tkproducts.com