

FEBRUARY 18, 2009

TRI-LASTIC

Product Information Statement for LEED® New Construction (NC) Version 2.2 Credit Documentation

TRI-LASTIC (TK-5610 Smooth, TK-5611 Fine Texture, TK-5612 Medium Texture, TK-5613 Coarse Texture) is a high quality 100% acrylic decorative and protective elastomeric coating for stucco, plaster, block, and other masonry substrates; and has excellent elongation and recovery properties, TRI-LASTIC will bridge hairline cracks and move with the substrate throughout a wide range of temperatures.

TK Products certifies the following information for TRI-LASTIC:

Manufacturing Location

TRI-LASTIC is manufactured in Minnetonka, MN.

Regional Materials

20% by weight of TRI-LASTIC was produced with regionally extracted and processed materials.

Recycled Content

TRI-LASTIC is manufactured with 6% combined recycled content.

VOC Content

TK Products certifies that the VOC (volatile organic content) of TRI-LASTIC is <70g/l.

Based upon the above information, TK Products certifies that TRI-LASTIC may contribute to the following LEED NC v2.2 Credits:

- MR Credits 4.1 & 4.2: Recycled Content: 10% & 20% (post-consumer + ½ pre-consumer)
- MR Credits 5.1 & 5.2: Regional Materials: 10% & 20% Extracted, Processed, & Manufactured Regionally
- EQ Credit 4.2: Low – Emitting Material: Paints and Coatings (referencing the South Coast Air Quality Management District (SCAQMD) Rule 1113, in effect on January 1, 2004)

Respectfully,



LEED Administrator
TK Products
Tel: 800-441-2129

LEED is a trade mark of the US Green Building Council