



TK-KWIK KLEAN

Stripper/Cleaner/Degreaser

Item No. TK-2012

PRODUCT DESCRIPTION

TK-KWIK KLEAN is a versatile, multi-purpose stripper, cleaner and degreaser for concrete surfaces.

Features:

- Removes curing and sealing compounds (acrylic resin based), carpet and vinyl floor adhesives, most forms of graffiti, and many forms of paint (latex, acrylic and dry fog).
- May also be used to clean stains, dirt and contamination from floors, walls and driveways.
- Supplied ready to use and requires no mixing or dilution.

USES:

Suitable for interior or exterior use on horizontal or vertical concrete surfaces such as floors, walls, driveways, walkways, etc.

APPLICATION PROCEDURES:

PREPARATION:

For proper application, the surface must be dry and free from extreme amounts of dirt or contamination. If the surface is excessively dirty, power wash and allow to dry thoroughly prior to application.

A test patch should be conducted prior to application to determine appropriate coverage rates, substrate compatibility and color.

MIXING:

The material is ready for use and requires no mixing or dilution.

APPLICATION:

Apply TK-KWIK KLEAN by spray, brush or roller at a rate of 200-300 square feet per gallon. The product is most effective when flooded onto the surface and kept wet for 5-10 minutes. If stains have not begun to dissolve or run off the surface within this time, reapply and use a stiff bristle brush or broom to aid in removal. Once clean, wipe with a clean cloth and rinse the area with soap and clean water.

Curing and Sealing Compound removal - Apply TK-KWIK KLEAN to the surface and allow to sit for 15-30 minutes before using a scraper to remove the compound. The surface should then be pressure washed to remove any remaining residue or contamination.

Graffiti Removal: Whenever anti-graffiti treated surfaces become vandalized, TK-KWIK KLEAN should be used to clean as it will soften and remove the graffiti without damaging the protective anti-graffiti membrane. *Important Safety Note:* The appropriate personal protective equipment is necessary to avoid injury during this process. Safety glasses/goggles and impervious gloves, at a minimum, are required. An appropriate NIOSH approved charcoal respirator is recommended for application in confined areas.

Wet the surface with TK-KWIK KLEAN by wiping or spraying it onto the surface. Frequently repeat this process for 15-20

TECHNICAL DATA

Composition and Materials:	A blend of limonene, ester and ketone
Color:	Clear
Flash Point:	117°F
Viscosity @ 77°F:	15-20 seconds Zahn #2
VOC Content:	8.14 lb/gallon
Applicable Standards:	This product is not currently regulated by 1999 Federal EPA VOC regulations

EFFECTIVENESS ON THESE SUBSTANCES:

Epoxies:	No
Urethane:	No
Latex Paint:	Yes
Curing Compounds:	Yes
Acrylic Sealers:	Yes
Grease/Oil:	Yes
Spray Paint:	Yes
Graffiti:	Yes
Silicones:	No
Adhesives:	Some

minutes to maintain a continually wet surface. Once the graffiti has softened sufficiently, wipe the surface with a clean rag that has been saturated in TK-KWIK KLEAN. Scrubbing will be required for heavily graffitied areas or on porous surfaces. Stubborn areas may require a second application of TK-KWIK KLEAN. A light power washing may be used to remove any remaining residue.

Safety Note: Place any residue in a closed metal container to avoid spontaneous combustion. Any soiled rags and waste should be soaked in a closed, water filled metal container immediately after use. This will prevent spontaneous combustion during temporary storage (prior to disposal).

CLEAN UP:

Clean tools, equipment and spills immediately with soap and water. Dispose of soiled rags in accordance with all applicable regulations.

COVERAGE:

Typical coverage rate is 200-300 square feet per gallon. Coverage rates are provided as a guideline only. Many factors including surface texture, porosity and weather conditions will determine actual coverage rates.

FIRST AID:

- Consult this product's safety data sheet for additional health and safety information. Safety Data Sheets are available through TK distributors, the TK office and the TK website.

AVAILABILITY:

TK-KWIK KLEAN is available through TK Distributors. Contact TK Products for the nearest distributor. Packaged in 55-gallon drums, 5-gallon pails, 1-gallon cans and quart containers.

FOR PROFESSIONAL USE ONLY

06/16 Last Rev. 03/15

CONDITIONS OF SALE/ LIMITED WARRANTY

TK Products, division of the Sierra Corporation, warrants that its products conform to the label descriptions, are free from manufacturing defects, and are fit for the ordinary purposes for which such goods are used. Inasmuch as the use of TK Products' product by others and other factors affecting product performance are beyond TK Products' control, TK Products does not guarantee the results to be obtained. There are no warranties except as stated herein, either express or implied, including implied warranties of merchantability or fitness for a particular purpose. **SHOULD ANY TK PRODUCTS' PRODUCT FAIL TO GIVE SATISFACTORY RESULTS, TK PRODUCTS WILL REPLACE THE PRODUCT, OR AT ITS OPTION, REFUND THE PURCHASE PRICE. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR ANY FAILURE OF TK PRODUCTS' PRODUCTS TO PERFORM AS WARRANTED AND SHALL ALSO CONSTITUTE LIQUIDATED DAMAGES IN CASE OF LOSS. UNDER NO CIRCUMSTANCES SHALL THE BUYER BE ENTITLED TO ANY OTHER REMEDY OR DAMAGES. REMEDIES FOR INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE SPECIFICALLY EXCLUDED.** TK Products does not authorize any person to assume for it any other liability in connection with the sale or use of its products unless specifically authorized by TK Products in writing.

TK DISCLAIMER:

Every effort has been made to ensure the accuracy of the above information and to avoid infringement of any patent or copyright. The information is based on field tests by government and private agencies, as well as lab tests, and on technical data from raw material manufacturers. The person(s) specifying or requesting the use of these products is responsible for assuring their suitability for a specific use, as well as the proper application of the products. Where there is any question as to the suitability of a particular product, a small test patch is recommended. See also CONDITIONS OF SALE/ LIMITED WARRANTY (Section 7) above.